



Valdisole 704-706 6th Street, Wynberg, Sandton, 2090
info@versuspaint.co.za | T: (011) 885 3136 | F: (011) 885 1719
www.versuspaint.co.za | www.paintwithapurpose.co.za | www.specifications.co.za

Versus Floor Paint

VFP

PRODUCT DESCRIPTION:

Premium quality tough UV stable floor coating for interior and exterior cement and concrete floor surfaces

USES:

- New or previously painted interior and exterior cement or concrete floors.
- Application to stoeps and window sills.

FEATURES:

- Alkali Resistant.
- Durability: Highly durable and UV resistant for the harsh South African climate.
- Excellent mechanical abrasion resistance.

PRODUCT INFORMATION:

- Type: Urethane resin.
- Appearance: Gloss.
- Colors: White and Grey.
- Solids: 50% – 60%.
- Viscosity at 25°C: 70 – 75 Krebs μ .
- Gravity: 0.85 – 1.00.
- Density: 1.10 – 1.20.
- Dry Film thickness: 150 Microns.
- Flash Point: 40°C.

APPLICATION DETAILS:

- Mixing: Stir well before use.
- Method: Brush or mohair roller. Application by brush ensures penetration.
- Thinning: Mineral Turpentine.
- Clean up: Mineral Turpentine.
- Spreading rate: 8-10 m²/l depending on surface porosity and profile.
- Conditions: Avoid painting in wet or cold weather. Minimum temp 8°C.
- Drying time: Touch dry 2 hours. Hard dry 16 hours at 25°C.
- Recoating time: 18 hours.
- Requirements: 2 coats.

SURFACE PREPARATION:

All Surfaces must be sound, clean and dry before painting.

- New and old concrete and cement surfaces:

Moisture content of new plaster must be less than 12%. Floors surfaces should be acid washed with Spirits of salt. Rinse well with clean water and allow drying.

Apply 2 coats of Versus Floor Paint.

- Previously painted floors in bad condition:

Strip surfaces thoroughly to remove all dirt and debris. Acid wash the floors with Spirits of salts. Rinse well and allow drying and apply 2 coats Versus Floor Paint.

- Previously painted floors in good condition:

Rub the surface down with sandpaper. Wash and rinse with clean water and allow drying and apply 1 or 2 coats of Versus Floor Paint.

STORAGE:

- Keep containers properly sealed.
- Store away from direct heat, sun and severe cold.

PACKAGING:

- 5 Litres.

PRECAUTIONS:

- Detailed safety information: refers to the material safety data sheet for this product.
- Do not apply to wet surfaces.
- Drying times will be extended during wet or cold weather conditions.

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.