



Valdisole 704-706 6th Street, Wynberg, Sandton, 2090
info@versuspaint.co.za | T: (011) 885 3136 | F: (011) 885 1719
www.versuspaint.co.za | www.paintwithapurpose.co.za | www.specifications.co.za



Versus Glass Beads VSB

DESCRIPTION

Iron Oxide pigments, marble aggregate and fillers dispersed in a pure acrylic emulsion.

SOLVENT TYPE

- Water

% Volume Solids – 68% ± 2

% Mass Solids – 82% ± 2

THEORETICAL SPREADING RATES

- 4kg/ m² – Paste
- 8Kg / m² – Glass

The figures are indicative and subject to applicator skill, substrate type and condition. Actual spread rates must therefore be determined by the applicator.

SOLVENT FOR CLEANING:

- Water

SHELF LIFE AND STORAGE

- 12 months in unopened containers. Store in a cool dry place

MATERIAL HANDLING AND SAFETY

- Versus Glass Beads & Versus Glass Beads Paste is non-hazardous and non-toxic; however the chemicals contained in the formula are irritants to mucous tissue. If the product gets into eyes wash with copious amounts of clean water. Do not induce vomiting if swallowed. Consult a physician if swelling or irritation persists.

TECHNICAL DATA

- Suitable for interior and exterior use
- Available in any colour
- Non-hazardous & non-toxic
- Trowel application
- Environmentally and user friendly.

SPECIFICATION

All of the coatings must be applied to a smooth, non-friable dry surface.

Surfaces must be prepared in accordance to SABS ISO 1514:1193 prior to the application of Versus Wall coatings. New walls must be cleaned and freed from any oil or gypsum. Corners and edges must be well defined. Prime surfaces with Versus Plaster Primer and fill all large holes and deep cracks with suitable filler to match existing surface.

DRYING TIMES

- Drying times: 25° C / 65% RH
- Surface Dry: 4 hours
- Hard Dry: 24 hours
- Over coating: 12 hours
- Fully Cures: 20-25 days

Note:

- Drying time will increase with decreasing temperatures. Approximately 10°C decrease = double drying time

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.