



Valdisole 704-706 6th Street, Wynberg, Sandton, 2090  
info@versuspaint.co.za | T: (011) 885 3136 | F: (011) 885 1719  
www.versuspaint.co.za | www.paintwithapurpose.co.za | www.specifications.co.za

## Versus Ripple Coat (Matt) VWRCM

### DESCRIPTION

Versus Ripple Coat (Matt): A new generation of 100 % pure acrylic textured plaster finish, using quartz aggregate, various fillers and colored with iron oxide pigments.

Versus Ripple Coat (Matt): is durable and flexible, aesthetically pleasing, maintenance free and has excellent adhesion.

- The product is body-color through Color fast, Ultra Violet resistant
- Water resistant
- Allows the walls to breathe
- Versus Ripple Coat (Matt): assists in the hiding surfaces imperfections / blemishes in the substrate, due to its thickness (1.5mm)
- Retains its elasticity (0,5mm per 10 cm of coating)
- Environmentally friendly < 13g / l VOC (Volatile Organic Compounds).
- Water based
- Low odor

### SURFACE PREPARATION

- Prepare substrate by removing all loose and friable matter.
- All surfaces need to be properly prepared / primed, as per manufactures specification\*\*
- Ensure that the plaster surface is clean, dry and sound and in accordance with SABS 1514:1993 plaster specification and C.C.I – SANS 2001- EMI: 2007 SUCCESSFUL PLASTERING, (605 ACCURACY)

### APPLICATION

- Versus Ripple Coat (Matt): is applied by ripple roller. This is a 2 coat application. Once the first coat is dry, a 2nd coat must be applied.
- The product is a premixed, therefore no adding of water / thinning is required.
- Note: Thinning will result in color variations.

### SUITABLE SURFACES

- Versus Ripple Coat (Matt): is suitable for interior and exterior, wall and ceiling surfaces.
- It can be applied to the following surfaces: Cement Plaster, Concrete, Gypsum (Rhinolite), Steel, Glass, OSB Board, Fibre cement board (Nutec), Wood.
- It can also be applied onto any previously painted surfaces.

### PACKAGING

- 35kg Pail or 300 KG DRUM

### SPREAD RATE

- 1.4Kg / M<sup>2</sup>
- Note: Spread rates should be used as a guide only, as the actual spread rates will vary depending on the surface.

### DRYING / CURING TIME

- 12- 24 Hours

Note: Dependent on ventilation and other climatic conditions.

### DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.

Do not apply if rain is expected within 4 – 6 hours of application.

### COLOUR RANGE

- It is available in any color
- Note: High pigment / bright colors will fade uniformly over time.

### CLEANING SOLVENTS

- Water

### ORDERS

- It is imperative that the correct quantity is ordered at the same time, to eliminate batch variance.
- Note: Versus Paint Specialists (Pty) Ltd cannot be held liable for any color variations, should insufficient quantities be ordered.
- Signed color sample panels are required prior to the manufacturing of product.

### STORAGE

- Keep containers properly sealed.
- Always store the container away from direct heat or sunlight.
- Note: Keep out of reach of children

### SHELF LIFE

- Minimum 12 Months, in an unopened container.

### FIRE RATING

- This product is water based and non-flammable.
- It has the lowest fire rating and will only burn as long as there is a flame.

### IMPORTANT

- All new, previously painted or unstable surfaces need to be primed / bonded with a suitable primer provided by Versus Paint Specialists (Pty) Ltd. (Please see preparation of surfaces)
- All horizontal surfaces need to be water-proofed; with Versus Versa-Proof (membrane is also recommended).

### APPLICATION NOTES

- Do not apply in direct sunlight.
- Recommended maximum panel size recommended for application, is 10M<sup>2</sup>.
- The entire panel is to be redone, should remedial work be required.
- Scaffold to be erected corner to corner, or from a v-joint to a v-joint, from a tape-joint to a tape-joint, or from a construction joint to a construction joint.
- Tape joints can be created, however they will need to be set out, marked, primed, painted with 2 coats Versus Aqua ripple and over coated in desired color, upon completion of coating application.

### BEST RESULTS

- For best results, the product should be applied by an experienced applicator.