



Valdisole 704-706 6th Street, Wynberg, Sandton, 2090  
info@versuspaint.co.za | T: (011) 885 3136 | F: (011) 885 1719  
www.versuspaint.co.za | www.paintwithapurpose.co.za | www.specifications.co.za

## Alta Marea Super Acrylic Mid Sheen VSAMS

### PRODUCT DESCRIPTION:

- A high quality mid sheen finish flexible wall coating for interior and exterior use, providing excellent durability, weather resistance, colour stainability, opacity and wash ability.
- Ideal for high traffic areas or surface that may be required frequent washing.

### PREPARATION:

- Surfaces must be clean and free from loose material.
- Surfaces must be primed correctly utilizing surface preparations specifications recommended by the manufacturers.
- May be applied directly onto clean previously painted surfaces.

### APPLICATION:

- With either a sheepskin roller or brush.
- Can be applied using an airless spray gun.

### PRODUCT INFORMATION:

- Type: Modified Acrylic.
- Water Resistance: Surpasses the SABS 044:1900 Code of practice rain
- Penetration test over a 24 hour period.
- Drying Time: Surface Dry ½ – 1 hour.
- Viscosity: 95-100 Kerb Units.
- Relative Density: 1.2 – 1.25 kg/l.
- Solid by Mass: 50-52%
- Spreading rate: 8-10m<sup>2</sup>/litre depending on surface porosity and texture.
- Finish: Mid Sheen
- Clean-up: Water
- Colour: White, Pastel, Medium and Deep Tone

### APPLICATION DETAILS:

- Mixing: Stir well before use.
- Method: Sheepskin roller or brush. Can be applied using an airless spray gun.
- Thinning: Not recommended, but tap water if required. Thinning reduces the opacity.
- Clean up: Tap water.
- Spreading rate: 8 – 10 m<sup>2</sup>/l depending on surface porosity and profile.
- Viscosity 95-100 Krebs  $\mu$
- Relative Density 1.2 – 1.25
- Conditions: Avoid painting in wet or cold weather.
- Minimum temp 8° C
- Drying time: Touch dry ½ – 1 hour. Hard dry 4 hours at 25 degrees.
- Recoating time: 4 – 6 hours.
- Requirements: 2 coats.

### STORAGE:

- Keep containers properly sealed.
- Store away from direct heat, sun and severe cold.

### PACKAGING:

- 5 litres and 20 litres

### PRECAUTIONS:

- Detailed safety information: refers to the material safety data sheet for this product.
- Do not apply directly to bare metal surfaces.
- Do not paint in wet or cold weather. (Minimum 8°C.)
- Drying times will be extended during wet or cold weather conditions.
- Do not apply direct to chalky or friable surfaces. Apply a penetrating coat of Versus Bonding Liquid or Versus Plaster Primer.

## DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.