



Valdisole 704-706 6th Street, Wynberg, Sandton, 2090  
info@versuspaint.co.za | T: (011) 885 3136 | F: (011) 885 1719  
www.versuspaint.co.za | www.paintwithapurpose.co.za | www.specifications.co.za



## Versus Anti Mosquito Paint VSAB

### PRODUCT DESCRIPTION:

A water based acrylic mosquito repellent coating for interior / exterior use.

### USES:

- Ideal for interior & exterior walls / ceilings.
- Suitable for correctly prepared new plaster.
- Suitable for correctly primed wood & metal surfaces.

### FEATURES:

- Water based: Low odor and easy cleaning.
- Highly durable and UV resistant for South African harsh climate.
- Quick drying.
- Repels mosquitoes for up to 3 years.in doors.On exterior surfaces, the duration of the repellent will be affected by ageing & weathering of the coating.
- Metal surfaces must first be primed.Do not apply to bare metal.
- Washable: Meets the requirements of the SABS and ASTM scrub resistant test methods.
- Good color stability.
- Non Yellowing: Unlike alkyd based paints whites and colors will not yellow.
- Water and steam resistant.
- Excellent resistance to spatter.
- Excellent adhesion, good flow and excellent opacity.
- Very low levels of VOC. 16g/Lt.

### PRODUCT INFORMATION:

- Type: Pure Acrylic.
- Appearance: Sheen.
- Colors: Available in a range of popular ready mixed colours.
- Solids: 35% by mass:21% by volume.
- S.G 1.2kg / Litre.
- Spread Rate 8 / 11 Meters 2 per litre per coat.Depend- ing on surface porosity and profile.
- Recommended Dry Film Thickness 35 um – 45 um
- Drying Time.Touch Dry 15 – 25 minutes @ 23 degree c.
- Dry to handle 1 Hour @ 23 degree c.
- Overcoating 1Hour @ 23 degree c.
- Viscosity 95 / 100 Ku @ 23 degree c.
- Flash Point.Non Flammable.

### APPLICATION DETAILS:

- Mixing: Stir well before use.
- Method: Short nap roller, brush or airless spray.
- Thinning: Not recommended. Thinning reduces the opacity. For spraying you can thin up to 10% with clean water.
- Clean up: Tap water.
- For best results ensure that all four walls as well as the ceilings are painted.

### SURFACE PREPARATION:

- New Surfaces must be sound, clean and dry before painting.
- Concrete and cement should be filled with Versus Versafill.
- Gypsum Plaster should be primed with Versus Plaster Primer.
- Fibre Cement ceiling boards: the bare metal areas (nail heads) should be primed with Versus Steel Primer.
- Wooden surfaces should be primed with Versus Pink Wood primer.
- Galvanized Iron should be cleaned first with Versus Galvanized Iron Cleaner until a water break free surface has been achieved. Thereafter prime with Versus Galvanized Iron Primer and followed with Versus Universal Undercoat.
- Rusted Metals should be wire brushed or sanded to remove all rust. Prime with Versus Steel Primer. Thereafter apply Versus Universal Undercoat.
- PVC gutters and downpipes should be degreased and then abraded with fine sandpaper and then the topcoat can be applied directly.
- Previously Painted Surfaces must be sound, clean and dry before painting.
- After all surfaces are sound, clean and dry apply one coat of Versus Universal Undercoat as a tie coat. Other areas that have chalked and are powdery should be well sanded and sealed with Versus Plaster Primer.

### STORAGE:

- Keep containers properly sealed.
- Store away from direct heat, sun and severe cold.

### PACKAGING:

- 5 litres and 20 litres

### PRECAUTIONS:

- Detailed safety information: refers to the material safety data sheet for this product.
- Do not apply directly to bare metal surfaces.
- Drying times will be extended during wet or cold weather conditions.
- Do not apply direct to chalky or friable surfaces.
- Do not apply before 9am and after 4pm in the winter.
- Do not apply exterior if it looks like rain will occur within 4-6 hours of application. Do not apply direct to chalky or friable surfaces.

### DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.