



Valdisole 704-706 6th Street, Wynberg, Sandton, 2090
info@versuspaint.co.za | T: (011) 885 3136 | F: (011) 885 1719
www.versuspaint.co.za | www.paintwithapurpose.co.za | www.specifications.co.za

Versus Eco-bebe VSEB

PRODUCT DESCRIPTION:

Eco – bebe baby paint is an eco – friendly paint that is suitable for your nursery ,cots & baby toys.

USES:

- These baby safe paints are non – toxic and low V.O.C.
- They can be used to create a delicate,non harmful finish to your babies environment.

FEATURES:

- Water based: Low odour and easy cleaning.
- Highly durable.
- Quick drying.
- Excellent wear resistance properties.
- Washable: Meets the requirements of the SABS and ASTM scrub resistant test methods.
- Mar and scratch resistant.
- Good color stability.
- Non Yellowing: Unlike alkyd based paints whites and colors will not yellow.
- Water and steam resistant.
- Excellent resistance to spatter.
- Excellent adhesion, good flow and excellent opacity.
- If correctly applied to a properly prepared substrate the product has a life expectancy of 7-10 years, possibly longer.
- Very low levels of VOC. 16g/Lt.

PRODUCT INFORMATION:

- Type: Pure Acrylic.
- Appearance: Sheen.
- Colors: Available in a range of popular ready mixed colors.
- Solids: 50% – 52% volume.
- Density: 1.2 – 1.4.
- Viscosity at 25°C: 95 – 100 Krebs μ .
- Flash Point: Non-flammable.

STORAGE:

- Keep containers properly sealed.
- Store away from direct heat, sun and severe cold.

APPLICATION DETAILS:

- Mixing: Stir well before use.
- Method: Short nap roller, brush or airless spray.
- Thinning: Not recommended. Thinning reduces the opacity. For spraying you can thin up to 10% with clean water.
- Clean up: Tap water
- Spreading rate: 8-10 m²/l depending on surface porosity and profile.

- Conditions: Avoid painting in wet or cold weather. Minimum temp 8° C
- Drying time: Touch dry ½ – 1 hour. Hard dry 3 hours at 25 degrees.
- Recoating time: 4-6 hours.
- Requirements: 2 coats.

SURFACE PREPARATION:

New Surfaces must be sound, clean and dry before painting.

Concrete and cement should be filled with Versus Versafill.

- Gypsum Plaster should be primed with Versus Water Plaster Primer.
- Wooden surfaces should be primed with Versus Water Based Pink Wood primer.
- Previously Painted Surfaces must be sound, clean and dry before painting.
- After all surfaces are sound, clean and dry apply one coat of Eco – bebe

PACKAGING:

- 5 litres and 20 litres

PRECAUTIONS:

- Detailed safety information: refers to the material safety data sheet for this product.
- Drying times will be extended during wet or cold weather conditions.
- Do not apply direct to chalky or friable surfaces.
- Do not apply before 9.00am and after 4 pm in winter.
- Do not apply direct to chalky or friable surfaces.

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.