



Valdisole 704-706 6th Street, Wynberg, Sandton, 2090
info@versuspaint.co.za | T: (011) 885 3136 | F: (011) 885 1719
www.versuspaint.co.za | www.paintwithapurpose.co.za | www.specifications.co.za



Versus Eggshell Enamel VEE

PRODUCT DESCRIPTION:

A top of the range durable interior solvent based paint with an eggshell finish for high traffic areas.

USES:

- Suitable for cement plaster, gypsum plaster, concrete, fiber cement, PVC, galvanized iron, ferrous and wooden surfaces.
- Finish for doors, frames, skirting and other trims.
- Ideal for bathrooms and kitchens.
- Final coat for primed interior cement plaster, hard-board, wood and metal.

FEATURES:

- Superb appearance. Does not highlight the imperfections.
- Ideal for kitchens and bathrooms, passages where cleaning is done often.
- Excellent flow and leveling.
- Easy application

PRODUCT INFORMATION:

- Type: Medium Oil Alkyd.
- Appearance: Eggshell.(Semi-Gloss)
- Colors: White and standard colors. Other pasteand medium tones can be tinted on request.
- Solids: 60-62% by mass.
- Density: 1.4- – 1.42 kg/l.
- Dry Film Thickness: Minimum 25 µ and maximum 30 µ.
- Viscosity at 25°C.: 70-75 Krebs µ.
- Flash Point: Non-flammable.

APPLICATION DETAILS:

- Mixing: Stir well before use.
- Method: Short nap mohair roller or brush.
- Thinning: Mineral Turpentine. Thinning not recommended except for application with spray.
- Clean up: Mineral Turpentine.
- Spreading rate: 8 – 10 m²/l depending on surface porosity and profile.
- Conditions: Avoid painting in wet or cold weather. Minimum temp 8° C
- Drying time: Touch dry 4 hours. Hard dry 18 hours at 25 degrees.
- Recoating time: 18 hours.
- Requirements: 2 coats

SURFACE PREPARATION:

- New Surfaces: must be sound, clean and dry before painting.
- Cement surfaces should be primed with 1 coat of Versus Plaster Primer. Follow with 1 coat of Versus Universal Undercoat and thereafter apply Versus Eggshell Enamel.
- Wooden surfaces should be primed with Versus Wood Primer. Follow with 1 coat Versus Universal Undercoat before applying the Versus Eggshell Enamel.
- Metal surfaces: Rust should be removed and then primed with 1 coat Versus Steel Primer and followed with 1 coat Versus Universal Undercoat before applying the Versus Eggshell Enamel.
- Previously painted Surfaces must be sound, clean and dry before painting.
- Loose flaking paint must be removed and bare areas should be spot primed with an appropriate primer before applying Versus Universal Undercoat and to finish with Versus Eggshell Enamel.

STORAGE:

- Keep containers properly sealed.
- Store away from direct heat, sun and severe cold.

PACKAGING:

- 1 Liter and 5 Litres. (20 Litres on request).

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.