



Valdisole 704-706 6th Street, Wynberg, Sandton, 2090
info@versuspaint.co.za | T: (011) 885 3136 | F: (011) 885 1719
www.versuspaint.co.za | www.paintwithapurpose.co.za | www.specifications.co.za



Versus Elegance Cementitious Coating VCF

PRODUCT DESCRIPTION:

A durable pigmented cementitious coating, which contains weather, ultra violet resistant chemicals and selfcuring properties.

USES:

- To provide a durable economic water resistant coating direct onto block or similar walls eliminating the need of plastering.
- To paint onto acrylic painted surfaces.
- Painting onto external plaster surfaces.
- High obliteration styrene acrylic based first coater designed for interior and exterior cement plaster.

FEATURES:

- Textured: Hides surface imperfections.
- Eco friendly, low VOC level.
- Water based: Low odor and easy cleaning.
- Water resistant: Prevents penetration of dampness.
- UV Resistant: Contains weather, UV resistant chemical and self-curing properties.
- A durable economic coating.

PRODUCT INFORMATION:

- Type: Cement based coating, reinforced with solid acrylic resin.
- Appearance: Natural aged finish.
- Colors: White and pastel shades by request.
- Recommended Dry Film Thickness: 200 μ per coat.
- Flash Point: Non-flammable.

APPLICATION DETAILS:

- Mixing: Stir well before use.
- Method: Sheepskin roller or brush.
- Thinning: Not recommended, but tap water if required. Thinning reduces the opacity.
- Clean up: Tap water.
- Spreading rate: 8m²/25Kg bag – depending on depth film thickness.
- Conditions: Avoid painting in wet or cold weather. Minimum temp 8° C.
- Drying time: Touch dry ½ – 1 hour. Hard dry 3 hours at 25 degrees.
- Requirements: 1 coat.

APPLICATION PROCEDURE /MIXING INSTRUCTIONS:

Brush application:

- To 10 liters of water, slowly add 25 kg Versus Elegance Cement Coating.
- Mix well to avoid the formation of lumps.
- Allow to stand for 10 minutes and use within 1 hour.

Trowel application:

- As for brush application, using only 6 liters of water.

Spray application:

- As for brush application using 7 liters of water.

Although cement paint is self-curing, it is recommended that to achieve a fast hard finish especially externally in hot dry conditions, the painted surface should be wet down three times during the day after the application. This will also help achieve an aged weathered look sooner.

SURFACE PREPARATION:

- New surfaces must be sound, clean and dry before painting Interior and exterior cement plaster – direct, no primer required.

Gypsum ceiling boards prime with 1 coat Versus Plaster Primer.

- Previously painted surfaces:
All paint that is powdered, soft, blistered, loose or flaking should be removed by scraping, wire brushing or sanding.
The surface should then be cleaned and allowed to dry.

STORAGE:

- Keep containers properly sealed.
- Store away from direct heat, sun and severe cold.

PACKAGING:

- 25 KG bags.

PRECAUTIONS:

- Detailed safety information: refers to the material safety data sheet for this product.
- Do not apply before the ambient temperature is above 8°C.
- Do not apply exterior of rain is expected with 4-6 hours of application.
- Drying times will be extended during wet or cold weather conditions.
- Do not apply direct to chalky or friable surfaces.

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.