



Valdisole 704-706 6th Street, Wynberg, Sandton, 2090  
info@versuspaint.co.za | T: (011) 885 3136 | F: (011) 885 1719  
www.versuspaint.co.za | www.paintwithapurpose.co.za | www.specifications.co.za



## Versus Interior Exterior Varnish Gloss VWVG

### PRODUCT DESCRIPTION:

A general purpose interior/exterior solvent based varnish for all wood surfaces.

### USES:

- For use on new and previously varnished interior and exterior wood surfaces.

### FEATURES:

- Excellent water resistance.
- Excellent exterior durability and very UV resistant.
- Durable wood varnish for all surfaces.

### PRODUCT INFORMATION:

- Type: A Long Oil Alkyd.
- Appearance: Matt and Gloss.
- Colors: Clear, Light Oak, Dark Oak, Teak, Mahogany.
- Solids: 45% by mass.
- Density: 0.82 - 0.86.
- Specific Gravity: 0.90 - 0.91.
- Viscosity at 25°C: 65-70 Kμ.
- Flash Point: Flammable at 34°C.

### APPLICATION DETAILS:

- Mixing: Stir well before use.
- Method: Brush. Rollers not recommended. Conventional spray.
- Thinning: Mineral Turpentine.
- Clean up: Mineral Turpentine.
- Spreading rate: 10-12m<sup>2</sup>/l depending on surface porosity and profile.
- Conditions: Avoid painting in wet or cold weather. Minimum temp 8° C
- Drying time: Touch dry 4 hours. Hard dry 18 hours at 25 degrees.
- Recoating time: 18 hours.
- Requirements: 2 coats.

### SURFACE PREPARATION:

New Surfaces must be sound, clean and dry (moisture content below 15%) before painting.

- Sand to a smooth surface in the direction of the wood fiber.
- Remove all dust.
- Thin first coat with 10% Mineral Turpentine.
- Sand slightly with fine sandpaper or fine steel wool in between coats.
- Apply 2nd coat and 3rd coat unthinned.
- To prevent ingress of moisture the end grain must be coated..

### REDECORATION:

- For surfaces in poor condition: Strip down and treat as new work.
- Surfaces in good condition must be slightly sanded, dusted and then treated as new work.
- For maximum protection on exterior wood 3 coats of varnish is advisable.

### STORAGE:

- Keep containers properly sealed.
- Store away from direct heat, sun and severe cold.

### PACKAGING:

1 Liter, 5 Litres, 20 Litres.

### PRECAUTIONS:

- Detailed safety information: refers to the material safety data sheet for this product.
- Not to be used as a wood floor coating.
- Do not apply on wet or damp timber.
- Do not paint in wet or cold weather. (Minimum 5°C.)
- Drying times will be extended during wet or cold weather conditions
- To prevent ingress of moisture the end grain must be coated..

### DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.