



Valdisole 704-706 6th Street, Wynberg, Sandton, 2090
info@versuspaint.co.za | T: (011) 885 3136 | F: (011) 885 1719
www.versuspaint.co.za | www.paintwithapurpose.co.za | www.specifications.co.za



Versus Matt Enamel

VME

PRODUCT DESCRIPTION:

A high quality enamel for use on various surfaces both internally and externally.

USES:

- Ideal for use on suitably primed interior plastered walls, wood and metal surfaces.

PRODUCT INFORMATION:

- Type: Long oil Alkid
- DFT/Coat: MIN 20UM. Max 30UM
- Colours: Available in white, Pastel, Medium and Dark Tones can be tinted on request.
- Drying Time: Surface dry 4 hours, Hard Dry 18 hours at 25°C.
- Viscosity: 65-70ku
- Specific Gravity: 1.08-1.2
- Spreading Rate: 8-10m²/l (Typical) depending on surface porosity and texture.
- Solids: 64-66% by mass
- Finish: Matt
- Clean Up: Mineral Turps

PREPARATION:

- Surface must be clean and free from loose material.
- New work should be correctly primed and undercoated with Versus Universal Undercoat as recommended by the manufacturers prior to applying the top coating.
- May be applied directly onto cleaned previously painted surfaces.

APPLICATION DETAILS:

- With either a short nap mohair roller or brush.
- Ensure that the product is well stirred and do not thin.

STORAGE:

- Keep container properly sealed after use.
- Keep away from direct sunlight, heat and severe cold.

PACKAGING:

- 5 litres and 20 litres

PRECAUTIONS:

- Do not apply to bare (unprimed) metal surface.
- Do not paint in wet or cold weather (Minimum 5°C)
- When coating friable or plastered surfaces apply a generous coat of Alkali Resistant Plaster Primer.

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.