



Valdisole 704-706 6th Street, Wynberg, Sandton, 2090
info@versuspaint.co.za | T: (011) 885 3136 | F: (011) 885 1719
www.versuspaint.co.za | www.paintwithapurpose.co.za | www.specifications.co.za



Versus Plaster Primer VPP

PRODUCT DESCRIPTION:

An alkali resistant solvent based penetrating primer for porous, friable and chalky surfaces.

USES:

- A good quality alkali resistant primer for use on new dry surfaces such as cement plaster, gypsum plaster, porous concrete, rhinolite and glass stone.
- For bonding and sealing on powdery, friable, very porous or stained substrates.
- For application on fire or nicotine stained areas.
- Ideal for both interior and exterior surfaces.

FEATURES:

- Excellent penetrating and binding properties.
- Pigmented white – time saving when top coating.
- Excellent adhesion.
- Excellent alkali resistant properties. Protects subsequent coats against alkali attack.
- Penetration into absorbent and chalky surfaces.
- Excellent stain blocking properties.
- Once sealed can be top coated with a wide range of Versus water and solvent based coatings.

PRODUCT INFORMATION:

- Type: Modified Alkyd Resin.
- Appearance: White.
- Colors: White.
- Density: 1.31 – 1.33.
- Viscosity at 25°C: 65 – 70 Kμ.
- Specific Gravity: 1.31 – 1.33.
- Solids: 75% by Mass.
- Flash Point: Flammable at 34°C.

APPLICATION DETAILS:

- Mixing: Stir well before use.
- Method: Brush or roller.
- Thinning: Mineral Turpentine.
- Clean up: Mineral Turpentine.
- Spreading rate: 10m²/l depending on surface porosity and profile.
- Conditions: Avoid painting in wet or cold weather. Minimum temp 8° C
- Drying time: Touch dry 4 hours. Hard dry 18 hours at 25 degrees.
- Recoating time: 18 hours.
- Requirements: 1 to 2 coats.

SURFACE PREPARATION:

- New Surfaces must be sound, clean and dry before painting. The moisture content must not be more than 15%. Apply 1 coat of Versus Plaster Primer. Work the product well into the surface.
- Previously painted surfaces: All powdery surfaces must be washed down and all loose and flaking paint must be removed. Apply 1 coat of Versus Plaster Primer. Work the product well into the surface.

STORAGE:

- Keep containers properly sealed.
- Store away from direct heat, sun and severe cold.

PACKAGING:

- 1Litre – 5 Litres - 20 Litres.

PRECAUTIONS AND LIMITATIONS:

- Detailed safety information: refers to the material safety data sheet for this product.
- Do not apply to metal surfaces.
- Drying times will be extended during wet or cold weather conditions.
- Do not apply on damp surfaces.

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.