



Valdisole 704-706 6th Street, Wynberg, Sandton, 2090  
info@versuspaint.co.za | T: (011) 885 3136 | F: (011) 885 1719  
www.versuspaint.co.za | www.paintwithapurpose.co.za | www.specifications.co.za



## Versus Versabond Bonding Liquid VPBL

**PRODUCT DESCRIPTION:**  
Clear Resin Based Bonding Liquid.

- USES:**
- For use as a clear alkali resistant sealer on gypsum plaster, cement plater and porous, friable concrete surfaces.
  - May also be used as a sealer for Masonite hardboard.

- PRODUCT INFORMATION:**
- Type: Urethane.
  - Drying Time: Surface dry 2 Hours at
  - Hard dry 8 Hours at 25°
  - Colors: Clear
  - Solids: ± 30%.
  - Specific Gravity: 0.80-0.82
  - Spreading Rate: 11-12m<sup>2</sup>/l (typical) depending on surface porosity and type.
  - Viscosity 15-18 Sec F4 @ 25°
  - Clean Up: Mineral turps.

- APPLICATION DETAILS:**
- Ready for use with roller or brush.
  - Application by brush ensures penetration.

- SURFACE PREPARATION:**
- New Surfaces all surfaces must be clean and dry. Moisture content of new plaster must be less than 12%
  - Previously Painted Surfaces must be brushed down and any loose flaking paint must be removed.

- STORAGE:**
- Keep containers properly sealed.
  - Store away from direct heat, sun and severe cold.

- PACKAGING:**
- 5 litres and 20 litres

- PRECAUTIONS:**
- Do not apply on metal surfaces.
  - Do not paint in wet or cold weather. (Minimum 5°C.)
  - Should be over coated within 48 hours to ensure adequate adhesion of the subsequent coats.

### DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.