



Valdisole 704-706 6th Street, Wynberg, Sandton, 2090
info@versuspaint.co.za | T: (011) 885 3136 | F: (011) 885 1719
www.versuspaint.co.za | www.paintwithapurpose.co.za | www.specifications.co.za



Versus Versafill VVF

PRODUCT DESCRIPTION:

A versatile flexible ready mixed hard drying filler for patching and fixing surface cracks.

USES:

- Interior and exterior cracks and gaps in walls.
- Blowholes in precast concrete.
- Skimming of uneven surface.
- Repairs to correctly primed Rhinolite.
- Defects in wood.
- Repairing cracked window putty.

FEATURES:

- Excellent adhesion properties.
- Easy to sand.
- Quick drying
- Excellent paintable surface.
- Suitable for interior and exterior use.
- Sets to a hard finish.
- Contains no toxic substances.

PRODUCT INFORMATION:

- Appearance: Paste.
- Colors: White
- Solids: 52% by mass.
- Density: 0.75 – 0.80.
- Recommended Dry Film Thickness: 1 - 10 mm.
- Flash Point: Non-flammable.

APPLICATION DETAILS:

- Mixing: Stir well before use.
- Thinning: Not recommended, but tap water if required.
- Clean up: Tap water.
- Spreading rate: 1m²/l @ 1mm thickness.

SURFACE PREPARATION:

- Remove all dust, debris, fungal- and algae growth.
- Clean out all holes, cracks and joints with a stiff brush.
- Seal all visible cracks with Versus Versafill and coat with Versus Plaster Primer.

PACKAGING:

- 1.75 Kgs and 7 Kgs.

PRECAUTIONS:

- Detailed safety information: refers to the material safety data sheet for this product.
- Do not apply exterior if it looks like rain will occur within 4 - 6 hours of application.
- Drying times will be extended during wet or cold weather conditions.
- This product is ready for use, preferably do not thin.
- Not formulated to fix up structural cracks.

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.