



Valdisole 704-706 6th Street, Wynberg, Sandton, 2090
info@versuspaint.co.za | T: (011) 885 3136 | F: (011) 885 1719
www.versuspaint.co.za | www.paintwithapurpose.co.za | www.specifications.co.za



Versus Versathane Polyurethane Enamel VVND

PRODUCT DESCRIPTION:

Premium quality tough low sheen polyurethane enamel for use on interior and exterior surfaces.

USES:

- Ideal for use on suitably primed plastered walls, wood and metal surfaces.
- The perfect product for bathroom walls and ceilings requiring a low sheen finish.
- Ideal for use on high traffic areas or surfaces that may require frequent washing.
- Ideal for painting doors, windows, cupboards and skirtings.

FEATURES:

- Easy to keep clean.
- Very tough and hardwearing.
- Lead free.
- Excellent exterior durability.
- Good color stability.
- Very good opacity, stain resistance and wash ability.
- Smooth low sheen finish for the interior.
- Excellent brush application sag resistant.

PRODUCT INFORMATION:

- Type: Polyurethane Alkyd.
- Appearance: Low Sheen.
- Colors: White, black and a range of colors. Pastel, Medium and Deep tone colors can be tinted on request.
- Solids: 61% by mass and 43% by volume.
- Density: 1.22.
- Recommended Dry Film Thickness: Minimum 25 µm and maximum 35µm.
- Specific Gravity: 1.22.
- Flash Point: Flammable at 34°C.

APPLICATION DETAILS:

- Mixing: Do not stir or thin as this will break down the gel structure.
- Method: Short nap mohair roller or brush.
- Thinning: Do not thin.
- Clean up: Mineral Turpentine.
- Spreading rate: 9 m²/l depending on surface porosity and profile.
- Conditions: Avoid painting in wet or cold weather. Minimum temp 8° C
- Drying time: Touch dry 1 hour. Hard dry 8 hours at 25 degrees.
- Requirements: 2 coats.

SURFACE PREPARATION:

New Surfaces must be sound, clean and dry before painting.

- Cement: Prime with 1 coat Versus Plaster Primer followed with 2 coats of Versus Versathane Polyurethane Enamel.
- Wooden surfaces: Apply Versus Pink Wood Primer followed with Versus Universal Undercoat prior to the application of 2 coats Versus Versathane Polyurethane Enamel.
- Rusted Metals should be wire brushed or sanded to remove all rust. Prime with Versus Steel Primer. Thereafter apply 2 coats of Versus Versathane Polyurethane enamel.
- PVC gutters and downpipes should be degreased and then abraded with fine sandpaper. Apply the topcoats.
- Previously Painted Surfaces must be sound, clean and dry before painting.

After all surfaces are sound, clean and dry apply one coat of Versus Universal Undercoat as a tie coat. Other areas that have chalked and are powdery should be well sanded and sealed with Versus Plaster Primer before applying 2 coats of Versus Versathane Polyurethane Enamel..

STORAGE:

- Keep containers properly sealed.
- Store away from direct heat, sun and severe cold.

PACKAGING:

- 1 Liter and 5 Litres.

PRECAUTIONS:

- Detailed safety information: refers to the material safety data sheet for this product.
- Do not apply directly to bare (unprimed) surfaces.
- Do not paint in wet or cold weather. (Minimum 5°C.)
- Drying times will be extended during wet or cold weather conditions.
- When coating is friable or plastered surfaces apply a generous coat of Versus Plaster Primer

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.